



ADECO® EXTRA GAS 10W-40

Product description:

ADECO EXTRA GAS 10W-40 is a high-quality, semi-synthetic, multigrade engine oil with high shear stability (stay in grade) used in gasoline engines and engines adapted for the use of liquefied petroleum gas (LPG) and compressed natural gas (CNG).

Purpose:

The engine ADECO EXTRA GAS 10W-40 is intended for lubrication of all types of modern gasoline engines and engines adapted for liquefied petroleum gas and compressed natural gas, installed in passenger and light delivery vehicles.

Main advantages:

- High motor protection at high loads and high temperatures;
- Easy engine start at low temperatures;
- Reduced oil consumption;
- Extended oil change interval (20000-30000 km depends on the car manufacturer's recommendation);
- Fuel saving
- Reduces engine wear, especially when using LPG;
- It guarantees perfect engine cleanliness

Physical and Chemical Properties:

<i>Characteristic, unit of measure</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15°C, g/cm ³	0,86 – 0,88	ASTM D 1298
Kinematic viscosity at 100°C, mm ² /s	13 – 15	ASTM D 445
Viscosity index	135	ASTM D 2270
Flash point, COC, °C	240	ASTM D 92
Pour point, °C	-30	ASTM D 97

Meets Specifications:

API SL/CF; ACEA A3/B3

Packaging: 1 l, 4 l, 60 l