



ADECO[®] TRAKTOL HT EXTRA SAE 10W-30

Product Description:

ADECO[®] TRAKTOL HT EXTRA SAE 10W-30, Superior Universal Tractor Transmission Oil (UTTO), is produced from selected, high quality base oils and complex additive packages which provide specifications needed to meet requirements for the lubrication of new generation tractors. This oil is developed according to the latest requirements of the world's leading tractors and transmissions manufacturers as John Deere, Massey Ferguson, Ford-New Holland and GM, Allison.

Purpose:

ADECO[®] TRAKTOL HT EXTRA 10W30 is intended for the lubrication of new generation tractors in which are functionally connected hydraulic, transmissions and wet brakes and the entire system is supplied with the same oil from a common or at the most two cases. It is suitable for use in construction and other off-road machines. DO NOT USE FOR THE ENGINE.

The Main Advantages:

- Very good lubrication and protection against wear and damage of all moving parts;
- Safe operation under all weather and exploitation conditions;
- Excellent thermal and oxidation stability;
- Good compatibility with sealing materials;
- Guaranteed protection against corrosion and rust;
- Minimum brake noise.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15 °C, g/cm ³	0,870	ASTM D 1298
Kinematic Viscosity at 100 °C, mm ² /s	8 – 10	ASTM D 445
Viscosity Index	145	ASTM D 2270
Flash Point, COC, °C	min 220	ASTM D 92
Pour Point, °C	max -35	ASTM D 97
Copper Corrosion, 3h, 100 °C	1a	ASTM D 130
Foaming: <ul style="list-style-type: none">• tendency, cm³• foam stability, cm³	20-50-20 0-0-0	ASTM D 892

Meet Specifications:

API GL-4; John Deere J20C/J20D; AGCO POWER FLUID 821XL; Ford ESN-M2C134-D; FNHA-2-C-201.00; FNHA 2-C-200.00; Case New Holland CNH MAT 3525/3505/3509; Massey Ferguson CMS M1145/1143/1141/1135; Allison C-4; Caterpillar TO-2.



Technical Data Sheet

Packaging: 10 L, 205 L