



ADECO ULTRA SYNTH SAE 5W-30

Product Description:

ULTRA SYNTH SAE 5W-30 is fully synthetic, high quality, multigrade engine oil, produced to meet high performances and protection in all operating conditions. Designed to meet the latest standards of leading engine manufacturers.

Purpose:

ADECO ULTRA SYNTH SAE 5W-30 is recommended for the lubrication of modern gasoline and diesel engines with turbocharger and computer computer controlled fuel injection, as well as for all modern multi-valve engines, engines with catalytic converter, vehicles with or without DPF filter which meet the requirements of the EURO 4 and EURO 5 emissions standards.

The Main Advantages:

- Safe engine protection at high loads and high temperatures;
- Decreased oil consumption;
- Extended oil drain interval;
- Impeccable engine cleanliness;
- Protection against wear and desposit formation;
- Fuel saving.

Fizičko-hemijska svojstva:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15°C, g/cm ³	0,84– 0,86	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	60 – 80	ASTM D 445
Kinematic Viskosity at 100°C, mm ² /s	10 – 12	ASTM D 445
Viscosity Index	140	ASTM D 2270
Flash Point, COC, °C	min 230	ASTM D 92
Pour Point, °C	max -40	ASTM D 97
Total Base Number, TBN, mgKOH/g	min 10	ASTM D 2896

Meet Specifications:

API SN/CF; ACEA A3/B4; MB 229.3; VW 502.00/505.00