



ADECO® ATF SUFFIX A

Product Description:

ADECO® ATF SUFFIX A is a mineral oil for the lubrication of automatic transmission systems of the older generation in passenger and commercial vehicles, agricultural, construction and mining machines.

Purpose:

ADECO® ATF SUFFIX A is intended for the lubrication of automatic transmission systems of motor vehicles and similar transmissions of agricultural and construction machines (automatic transmissions, hydraulic control systems, hydraulic clutches, torque converters, of trucks, etc.) of older generations, where the quality level of GM Suffix A is required.

The Main Advantages:

- Good protection against wear and sliding;
- Very good oxidation stability;
- Maintains the same properties at different operating temperatures.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15 °C, g/cm ³	0,860 – 0,870	ASTM D 1298
Kinematic Viscosity at 40 °C, mm ² /s	40 – 42	ASTM D 445
Kinematic Viscosity at 100 °C, mm ² /s	7 – 8	ASTM D 445
Viscosity Index	145	ASTM D 2270
Pour Point, °C	-40	ASTM D 97
Flash Point, COC, °C	min 190	ASTM D 92

Meet Specifications:

GM Type A Suffix A; MB 236.2; Allison C-4; Caterpillar TO-2; Ford M; ZF TE-ML 09; MAN 339 Type A; Volvo 97325.

Packaging: 1 L, 60 L, 205 L