



ADECO® EKOKLINER

Product Description:

ADECO® EKOKLINER is produced from naphtenic raffinates and solvents, with the addition of special additive packages and emulsifiers, which enable efficient dissolution of grease and water rinsing.

Purpose:

A special cleaner ADECO® EKOKLINER is used for cleaning and degreasing of all kinds of metal, engines, transmission elements, gear transmissions and for the removal of greased and oiled impurities from the floors in mechanical workshops, as well as from the other stained surfaces.

Usage:

Use a brush, mop or spray to soak greased and oily surface. Allow it to stand for a few minutes to half an hour depending on the thickness of the fat deposits and then rinse it with lukewarm (warm) water.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15 °C, g/cm ³	0,79	ASTM D 1298
Kinematic Viscosity at 20 °C, mm ² /s	1,50 – 2,00	ASTM D 445
Solubility in water	meets	
Total Acid Number, TAN, mgKOH/g	max 0,1	ASTM D 664
Flash Point, Pensky-Martens, °C	min 50	ASTM D 93
Pour Point, °C	-50	ASTM D 97

Packaging: 750 mL, 1 L, 5 L, 200 L