



LANC LUB

Product Description:

ADECO® LANC LUB is mineral oil for the lubrication of chains of all types of chainsaws. With characteristics of high lubricity and adhesion, this oil protects against wear and corrosion, what provide extended service life of chains and reduce oil consumption. High viscosity index enables equally use in summer and winter conditions, while retaining all of its properties.

Purpose:

ADECO® LANC LUB is intended for the lubrication of chains of all types of chainsaws which have wide application in forestry and wood processing industry in difficult operating conditions, under different temperature conditions (winter - summer), in conditions of different humidity, in the presence of water, snow, dust and mud.

Physical and Chemical Properties :

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15°C, g/cm ³	0,88 – 0,90	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	80 – 120	ASTM D 445
Kinematic Viscosity at 100°C, mm ² /s	10,5 – 11,5	ASTM D 445
Viscosity Index	95	ASTM D 2270
Flash Point, COC, °C	min 210	ASTM D 92
Pour Point, °C	-12	ASTM D 97

Note:

Store oil in original packaging, and in area protected from moisture and fire. It must not be used as an oil for two-stroke engines, i.e. to make a gasoline mixture for engines.

Packaging: 1 L, 5 L, 200 L