



# ADECO® PNEUMATIK OIL 10

### **Product Description:**

ADECO® PNEUMATIK OIL 10, lubricating oil for components of pneumatic systems, which contain the deemulgator, which allows the extraction of the water from the oil, or for drying process air.

### **Purpose:**

ADECO® PNEUMATIK OIL 10 is used for lubricating components of pneumatic systems with oil mist, that is, by compressed air, as an energy medium, enriched with oil particles.

It is used for lubrication in the system with the return of the lubricant to the reservoir after the lubrication and in the system in which the lubricant does not return after the lubrication, but goes to the environment. The oil is poured into a specially provided oil tank. The oil level is regularly checked and, if necessary, refilled.

### **Physical and Chemical Properties:**

<b><i>Characteristic, Unit</i></b>	<b><i>Referential value</i></b>	<b><i>Metoda</i></b>
Density at 20°C, g/cm <sup>3</sup>	0,888 – 0,895	ASTM D 1298
Kinematic Viscosity at 20°C, mm <sup>2</sup> /s	18 – 34	ASTM D 445
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s	8 – 15	ASTM D 445

**Meet Specifications:** ISO 6743/11 L-P; DIN 51502

### **Packaging:**

5L , BULK