



ADECO[®] SUPER GAS SAE 15W-40

Product Description:

ADECO SUPER GAS SAE 15W-40 is multigrade motor oil, manufactured from highly refined base oils and selected additives, that provide excellent protection against oxidation and nitration, as well as the formation of deposits in the engine.

Purpose:

ADECO SUPER GAS SAE 15W-40 is intended for the lubrication of passenger vehicles and light trucks, which are fueled by LNG (liquefied natural gas) and gasoline. Provides excellent engine lubrication, as well as engine protection from high temperature generated by the combustion of LNG.

The Main Advantages:

- Excellent engine protection against oxidation, nitration and wear in all operation condition;
- Extended service life of the engine and spark plugs;
- Using of LNG exclusively, extended oil change interval by 50% is provided.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15°C, g/cm ³	0,80 – 0.90	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	100 – 110	ASTM D 445
Kinematic Viscosity at 100°C, mm ² /s	13 – 16	ASTM D 445
Viscosity Index	110	ASTM D 2270
Flash Point, COC, °C	min 200	ASTM D 92
Total Base Number, TBN, mgKOH/kg	8	ASTM D 2896

Meet Specifications:

API SL/CF; ACEA A3/B3; Cummins CES 20074; Detroit Diesel DDC 93K216.

Packaging: 1 L