



ULTRA 5W-30

Product Description:

ULTRA 5W-30 is synthetic multigrade engine oil, produced to meet high performances and protection in all operating conditions.

Purpose:

ULTRA 5W-30 is recommended for the lubrication of modern gasoline and diesel engines with turbocharger and computer controlled fuel injection, as well as for all modern multi-valve engines, engines with catalytic converter, vehicles without DPF filter which meet the requirements of the EURO 4 and EURO 5 emissions standards.

The Main Advantages:

- Safe engine protection at high loads and high temperatures;
- Decreased oil consumption;
- Extended oil drain interval;
- Impeccable engine cleanliness;
- Protection against wear and desposit formation;
- Fuel saving.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
Density at 15°C, g/cm ³	0,845 – 0,855	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	65 – 75	ASTM D 445
Kinematic Viskosity at 100°C, mm ² /s	10 – 12	ASTM D 445
Viscosity Index	160	ASTM D 2270
Flash Point, COC, °C	min 230	ASTM D 92
Pour Point, °C	max -40	ASTM D 97
Total Base Number, TBN, mgKOH/g	8	ASTM D 2896

Meet Specifications:

API SL