



# ADECO ULTRA SYNTH SAE 5W – 40

### Product Description:

ULTRA SYNTH SAE 5W-40 is high quality synthetic multigrade engine oil, formulated to meet high performances and protection of modern engines in all operating conditions. Designed to meet the latest standards of leading world's and European engine manufacturers.

### Purpose:

ADECO ULTRA SYNTH SAE 5W-40 is recommended for the lubrication of gasoline and diesel engines of passenger cars, light commercial vehicles, i.e. modern engines with turbocharger and computer injection control, as well as for all modern multi-valve diesel engines, engines with catalyst, vehicles with or without DPF filter that meet the requirements of the EURO 4 and EURO 5 emission standards in harsh climatic conditions.

### The Main Advantages:

- Reliably engine protection at high loads and high temperatures;
- Easy engine start at low temperatures;
- Reduced oil consumption due to low volatility;
- Impeccable engine cleanliness;
- Long service life of catalyst;
- Extended oil drain interval and fuel saving.

### Physical and Chemical Properties:

<b>Characteristic, Unit</b>	<b>Referential Values</b>	<b>Method</b>
Density at 15°C, g/cm <sup>3</sup>	0,845 – 0,855	ASTM D 1298
Kinematic Viscosity at 40°C, mm <sup>2</sup> /s	75 – 85	ASTM D 445
Kinematic Viskosity at 100°C, mm <sup>2</sup> /s	13 – 16	ASTM D 445
Viscosity Index	160	ASTM D 2270
Flash Point, COC, °C	min 225	ASTM D 92
Pour Point, °C	max -40	ASTM D 97
Total Base Number, TBN, mgKOH/g	8	ASTM D 2896
Foaming, ml/ml: Sekvenc I Sekvenc II Sekvenc III	10/0 50/0 10/0	ASTM D 892



## Technical Data Sheet

---

### **Meet Specifications:**

API SN/CF; ACEA A3/B4; MB 229.3/229.5; VW 502.00/505.00; PORSCHE A40; Opel LL-A/B-025

**Packaging:** 1 L, 4 L, 60 L, 205 L