

ADECO® 2T MIX UNIVERZAL

Product Description:

Oil for two-stroke engines, produced from selectively and hydro refined base oils, ashless additives and appropriate solvents.

Purpose:

Mineral engine oil ADECO® 2T MIX UNIVERZAL is intended for the lubrication of two-stroke gasoline engines with air cooling volume from 20 ccm to 500 ccm. Recommended for the lubrication of cultivators, lawnmower, chainsaws, mopeds, motorcycles, aggregates and similar 2T engines.

Ensures continuous operation of the engine without spark plugs bridging, without sludge formation on the piston and exhaust vents. This performance enables longer engine life and improved fuel economy in harsh conditions. It is suitable for the preparation of the mixture gasoline in 1:50 ratio, i.e. 2% oil, or according to the recommendation by engine manufacturer. Recommended for the lubrication of engines by manufacturers such as Husqvarna, Stihl, Tomos, etc.

The Main Advantages:

- Outstanding lubricity;
- Outstanding engine rinse;
- Minimal energy losses on engine start;
- Reduced smoke content in exhaust gases;
- Maintains cleanliness and condition of exhaust pipe.

Physical and Chemical Properties:

Characteristic, Unit	Referential Values	Method
Density at 15°C, g/cm ³	0,87 – 0,88	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	40 – 42	ASTM D 445
Kinematic Viscosity at 100°C, mm ² /s	6 – 7	ASTM D 445
Viscosity Index	120	ASTM D 2270
Flash Point, COC, °C	min 80	ASTM D 92
Pour Point, °C	-24	ASTM D 97
Copper Corrosion	1b	ASTM D 4048
Anticorrosive Properties (presence of water)	Meets	
Sulfated Ash, %	0,12	ASTM D 874

Meet Specifications:

API TC; JASO FC; ASTM TSC-3; ISO L-EGC.

Packaging: 100 mL, 500 mL, 1 L, 60 L, 205 L