



ADECO® 2T SYNTECH

Product Description:

ADECO® 2T SYNTECH is fully synthetic engine oil, very high quality.

Purpose:

ADECO® 2T SYNTECH is intended for the lubrication of two-stroke new generation engines of chainsaws, lawnmowers, motorcycles, outboard engines, water pumps, etc., which are fueled with mixture of oil and gasoline (Super 98 / Unleaded BMB 95).

Especially recommended for two-stroke engines operating under high loads for several hours. Remarkable lubricity and engine protection against wear at maximum loads. Also, prevents formation of coke deposits and soot in the engine and prevents the effect of self-ignition of the mixture.

The Main Advantages:

- Excellent lubricity;
- Excellent combustion of the mixture without smoke;
- Very good engine protection from the formation of sludge and soot;
- Reduced emission of exhaust gases;
- Very good mixing with fuel.

Physical and Chemical Properties:

Characteristic, Unit	Referential Values	Method
Density at 15°C, g/cm ³	0,845 – 0,850	ASTM D 1298
Kinematic Viscosity at 40°C, mm ² /s	60 – 80	ASTM D445
Kinematic Viscosity at 100°C, mm ² /s	8 – 10	ASTM D445
Viscosity Index	100	ASTM D 2270
Flash Point, COC, °C	200	ASTM D 92
Pour Point, °C	-24	ASTM D 97
Copper Corrosion	1b	ASTM D 4048
Anticorrosive Properties (presence of water)	Meets	

Mixing with fuel according to the recommendation by the engine manufacturer and the most frequently in 1:50 ratio, i.e. 2% - 3% oil.

Meet Specifications:

API TC; JASO FD; ISO-L-EGD; TISI.

Packaging: 100 mL, 500 mL