



ADECO[®] 4T SAE 30 PLUS

Motor oil for four-stroke gasoline engines with air cooling

Product Description:

ADECO[®] 4T SAE 30 PLUS is a real grade of SAE 30 engine oil, prepared for small air-cooled four-stroke engines. Contains a well balanced mixture of selected, high quality base oils and additive packages. Developed to provide unexcelled wear protection, engine cleanliness and oxidation stability, as well as constant oil viscosity at different exploitation temperatures. Most of small gasoline engines have an oil crankcase capacity of 600 ml, that is ours rationally oil package. This eliminates unnecessarily storage of oil excess – i.e. oil spilling.

Purpose:

ADECO[®] 4T SAE 30 PLUS engine oil is prepared for the lubrication of small air-cooled gasoline engines of lawnmowers, cultivators, tractors, compressors, aggregates and similar engines where is recommended 4T engine oil of SAE 30 grade and the API SJ specification quality level. Without official permission for using, but suitable for use in engine by manufacturers such as Briggs & Stratton, Kubota, Clinton, Honda, Onan, Homelite, Tecumseh, Kawasaki, Wisconsin, Kohler and similar.

The Main Advantages:

- Decreased wear and extended engine life;
- Engine protection in difficult operating condition and exploitation;
- Removes harmful deposits from vital engine parts;
- Engine protection from rust and corrosion;
- Practic package for 4T engine easy usage;
- Meets API SL and SJ specification.



Technical Data Sheet

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>	<i>Method</i>
SAE Viscosity Grade	30	SAE J300
Density, °API	29,9	ASTM D 287
Density at 15°C, g/cm ³	0,87 – 0,88	ASTM D 1298
Viscosity at 40°C, cSt	80 – 100	ASTM D 445
Viscosity at 100°C, cSt	10 – 11	ASTM D 445
Viscosity at 100°F, SUS	410 – 420	ASTM D 445; D 2161
Viscosity at 210°F, SUS	55 – 65	ASTM D 445; D 2161
Flash Point, COC, °C	min 210	ASTM D 92
Pour Point, °C	max -25	ASTM D 97
Color	6	ASTM D 1500
Sulfated Ash, %	1	ASTM D 874

Meet Specifications:

API SJ

Packaging: 600 mL