



ADECO® CLASSIC

Product Description:

Multigrade engine oil ADECO® CLASSIC is produced from quality base oils and additive packages that enable better engine protection against wear, corrosion, oxidation and deposit formation. Its standard alkalinity neutralizes the acidic products of fuel combustion. It is produced in two SAE viscosity grades: 15W-40 i 20W-50.

Purpose:

Multigrade engine oils ADECO® CLASSIC SAE 15W-40 and SAE 20W-50 are intended for operation in mixed fleets, for diesel engines and gasoline engines of older generation.

The Main Advantages:

- Good protection against wear, corrosion and oxidation of vital engine parts;
- Good detergent properties which enable extended engine service life;
- Prevention of a deposit formation at low and high temperatures;
- Enabled diesel engine operation in difficult conditions.

Physical and Chemical Properties:

<i>Characteristic, Unit</i>	<i>Referential Values</i>		<i>Method</i>
	15W-40	20W-50	
SAE Viscosity Grade			
Density at 15°C, g/cm ³	0,870 – 0,880	0,880 – 0,890	ASTM D 1298
Kinematic Viscosity at 100°C, mm ² /s	11 – 13	14 – 16	ASTM D 445
Viscosity Index	110	110	ASTM D 2270
Pour Point, °C	-15	-15	ASTM D 97
Total Base Number, TBN, mgKOH/kg	6	6	ASTM D 2896

Meet Specifications:

API CC/SC

Packaging: 1 L, 4 L, 10 L, 205 L