



ADECO® EXTRA SYNTH 10W- 40

Product Description:

ADECO® EXTRA SYNTH 10W- 40 is universal semi synthetic multigrade high shear stability (stay in grade) motor oil used in high performance gasoline and diesel engines with direct fuel injection, as well as for extended oil change intervals according to the engine manufacturer's recommendations. HTHS > 3,5mPa·s, SA ≤1,6%.

Purpose:

Engine oil ADECO EXTRA SYNTH 10W-40 is intended for the lubrication of all types of modern gasoline and diesel engines of passenger vehicles with and without catalysts and turbochargers, as well as light trucks manufactured in the period from 2001 to 2004. Especially recommended for multi-valve engines.

The Main Advantages

- Reliably engine protection at high loads and temperatures;
- Easy engine start at low temperatures;
- Decreased oil consumption;
- Extended oil change interval (20000-30000 km, depending on recommendation of automotive manufacturer);
- Fuel saving.

Physical and Chemical Properties:

Characteristic, Unit	Referential Values	Method
Density at 15°C, g/cm ³	0,86 – 0,89	ASTM D 1298
Kinematic Viscosity at 100°C, mm ² /s	13 – 16	ASTM D 445
Viscosity Index, min	min 120	ASTM D 2270
Flash Point, COC, °C	min 240	ASTM D 92
Pour Point, °C	max -30	ASTM D 97
Total Base Number, TBN, mgKOH/g	10	ASTM D 2896

Meet Specifications:

API SN/CF; ACEA A3/B4; MB 229.3; VW 502.00/505.00/501.00; Renault RN0700/0710; PSA B712300

Packaging: 1 L, 4 L, 60 L